

520, 452
PCT 05 JAN 2005
(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/008737 A1

(51) International Patent Classification⁷: H04N 1/60

(21) International Application Number:
PCT/EP2003/050298

(22) International Filing Date: 9 July 2003 (09.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02102020.1 10 July 2002 (10.07.2002) EP
60/406,450 28 August 2002 (28.08.2002) US

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): MAHY, Marc
[BE/BE]; AGFA-GEVAERT, Corporate IP Department,
Septestraat 27, B-2640 Mortsel (BE). VERBEECK,
Francis [BE/BE]; AGFA-GEVAERT, Corporate IP De-
partment 3800, Septestraat 27, B-2640 Mortsel (BE).

(81) Designated States (*national*): JP, US.

(84) Designated States (*regional*): European patent (DE, FR,
GB).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(71) Applicant (*for all designated States except US*):
AGFA-GEVAERT [BE/BE]; Septestraat 27, B-2640
Mortsel (BE).

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: SYSTEM AND METHOD FOR REPRODUCING COLORS ON A PRINTING DEVICE

(57) Abstract: A method and a system for outputting an image having a specific color on an output device, the method including (a) analyzing the image; (b) creating a model for the output device, based on the analysis, wherein the model encompasses the specific color and is made in a particular space having a one-to-one relation to a device independent color space.

WO 2004/008737 A1

[DESCRIPTION]

FIELD OF THE INVENTION

5 SYSTEM AND METHOD FOR REPRODUCING COLORS ON A PRINTING DEVICE

The present invention relates to methods and apparatuses for the reproduction of color documents; the invention especially concerns color management. The invention is particularly suitable for the reproduction of objects defined by a mixture of process inks and non-process inks.

BACKGROUND OF THE INVENTION

15

Today, more and more output systems are developed for the reproduction of color images. Several display and printing technologies are used such as CRT's, LCD's, conventional photography, electrophotography, thermal transfer, dye sublimation and ink jet systems to name a few. In the rest of this document, these systems will be referred to as output devices.

All these systems can be described as multi-dimensional color devices with n colorants such as CMYK (cyan, magenta, yellow and black) inks of an ink jet system or RGB (Red, Green, Blue) in case of a display system. In this document it is assumed that the colorant values for printers range from 0% (no colorant laid down on paper) to 100% (maximum amount of colorant laid down on paper). For display systems, the values range from 0 to 255. In the rest of this document, mainly a printer will be used as an example of an output system, however, it is well known in the art of color management systems that all aspects of printers can be easily extended to those of display systems.

35 With colorant space is meant an n -dimensional space, wherein n is the number of independent variables with which the output device can

be addressed. For an offset printing press e.g., the dimension of the colorant space equals the number of inks of the printing press. If CMYK inks are used, the dimension of the colorant space is four. Colorant spaces are also referred to as device dependent spaces.

5

The colorant gamut is defined by all possible combinations of colorant values, ranging from 0% to 100% for printers and from 0 to 255 for display systems, taking into account a number of specified colorant limitations. If there are no colorant limitations, the
10 colorant gamut is an n-dimensional cube.

With colorimetric space is meant a space that represents a number of quantities of an object that characterize its color. In most practical situations, colors will be represented in a 3-dimensional
15 space such as the CIE XYZ space. However, also other characteristics can be used such as multi-spectral values based on filters that are not necessarily based on a linear transformation of the color matching functions. The values represented in a colorimetric space are referred to as colorimetric values. Colorimetric spaces are also
20 referred to as device independent spaces or as color spaces.

A printer model is a mathematical relation that expresses colorimetric values in function of colorants for a given output system. The variables for the colorants are denoted as c_1, c_2, \dots, c_n with
25 n the dimension of the colorant space. An n-ink process is completely characterized by its colorant gamut with a number of colorant limitations and the printer model. Because of this close relationship between an n-ink process and the printer model, the operations typically defined for a printer model are easily extended
30 to an n-ink process.

The printer model is often based on a printer target. Such a target consists of a number of uniform color patches, defined in the colorant space of the printing device. In a next step the printer
35 target is printed and measured, and based on the values of the patches in colorant space and the measured colorimetric values, the

printer model is made. A printer target is normally characterized by a number of sampling points along the different colorant axes. Based on the sampling points a regular grid can be constructed in colorant space of which a number of grid points are contained by the printer target. Hence a target can be said to be complete or incomplete. We refer to patent application **EP-A-1 146 726** for more information on grids, complete and incomplete printer targets, and related terms.

With inverting an n-ink process is meant that the corresponding printer model is inverted. The transformation of an n-ink process to colorimetric space on the other hand is equivalent to the transformation of the corresponding colorant gamut to color space by making use of the printer model.

We refer to patent application **EP-A-1 083 739** for more information on colorant spaces, color spaces, and other relevant terms.

Based on a printer model, forward and inverse look up tables are constructed. These tables are also referred to as tables or color tables. A forward table transforms colorant values to colorimetric values whereas the inverse tables transforms colorimetric values to colorant values. Inverse tables are also called separation tables or color separation tables.

The present invention is related to the rendering of page descriptions, consisting of multiple page elements such as text, different types of images and color gradations (color gradations, also called color vignettes, are elements wherein color smoothly changes from one color to another one).

30

In most cases, the page elements are described in a colorimetric or colorant space, which may either be a device independent color space such as CIELAB, or a device dependent space such as RGB or CMYK. If the page has to be reproduced on a given output system, such as a printer or a display system, the color values have to be transformed to the proper colorant values of the concerned output system. This

transformation is required as the color space of the page elements is in most cases different from the color space of the output system. In fact for most documents it is not known in advance on which output system the document will be reproduced and the
5 different page elements may be defined in different color spaces. Hence to reproduce these page elements, each element is preferably color managed by making use of proper color transformations.

10 In a lot of cases, all page elements are defined in the same conventional color space. Depending on the application, this is usually a device dependent RGB, CMY or CMYK space. In home office environments, the RGB space corresponds to a monitor space and preferably the sRGB space is used. In a graphic arts environment, the CMYK values are typically standard Euro, SWOP or standard
15 newspaper colorant values.

If the output system is known on which the document has to be reproduced, the color values have to be transformed unless the color space of the page elements corresponds to the color space of the
20 output device. Such a transformation is in most cases done with color tables. A worldwide-accepted system to transform the colors is given by the ICC, the International Color Consortium. With this approach, each device is characterized to or from a device dependent color space. Such a transformation is described by tables, matrices
25 and TRC's (Tone Reproduction Curves, i.e. one-dimensional look up tables) which are stored in a profile. In most cases profiles contain both forward and inverse color tables. Hence, if all page elements have the same color space, profiles can be used to perform the proper color management operations.

30

If on the other hand different page elements are defined by different but conventional color spaces, and these spaces can be described properly by conventional profiles, then the ICC approach can also be applied easily. To support this functionality, different
35 applications allow the embedding of profiles in images.

For a number of page elements, however, ICC profiles do not yield good results. This is the case when non-process colors or a combination of process and non-process colors are used. Process colors are the colorants used in conventional printing processes such as CMYK for normal offset printing, or cyan, magenta, yellow, black, orange and green in case of HexachromeTM printing. In addition to process colors, non-process colors may be used, such as custom colors and spot colors. A custom color is a colorant especially created for a particular application. Spot colors on the other hand are colorants that are typically used if images are created artificially. The designer of the image then chooses one or more spot colors to render some image portions more accurately. In practice, a spot color is chosen out of a set containing tenths or hundreds of colorants. Spot colors are also called named colors.

Since a spot color is chosen out of a very large set of colorants, it is not practical to make color tables to describe the mixing of one or several spot colors.

As only the colorimetric values of the 100 % patch are known, a spot color is usually rendered by transforming the colorimetric values of the 100 % patch to the colorant values of the output device. By making use of simple interpolation techniques, colorant values for in between dot percentages of the spot color can be obtained.

More complicated is the situation in which multiple spot colors, or spot colors and process colors are printed on top of each other. Due to the very large number of possible color combinations, it is practically impossible to print the most elementary combinations in order to be able to construct an accurate printer model.

Therefore, if spot colors are printed on top of each other, it is customary to calculate the overlap simply by adding the colorant values of the individual spot colors. Take for example an overlap of 40 % of a first spot color and 70 % of a second spot color, and suppose that the colorant space of the output device is CMYK. The

CMYK colorant values of the 40 % patch are determined from values of the 100 % patch of the first spot color, and those of the 70 % patch are determined from the 100 % patch of the second spot color. The color of the overlap is then predicted by adding the CMYK values of the 40 % and those of the 70 % patch. However, this solution is not accurate.

There is thus a need for an improved method.

10

SUMMARY OF THE INVENTION

The present invention is a method for outputting an image on an output device as claimed in independent claim 1 and a system as claimed in independent claim 21. Preferred embodiments of the invention are set out in the dependent claims. Preferably, a method in accordance with the invention is implemented by a computer program as claimed in claim 16.

20 In an embodiment of the present invention, a dedicated printer model is created describing the color mixing of a non-process color with a given number of non-process colors and/or process colors. To build the model, the colorant combinations of the image need to be known. In a preferred embodiment of the invention, the image is therefore analyzed, and the model is created, based on the analysis. One or more image characteristics may be extracted from the image and used in creating the model.

30 As mentioned above, customarily a printer model is created before the image is processed. Usually the printer model is based on a printer target that is printed by means of the process colors, which are often CMYK. The printer model is then used in reproducing portions of images that are composed of process colors. As mentioned above, for image portions wherein non-process colors are used, a second, very simple approach is used wherein the non-process

35

colors are converted to CMYK and, in case of overlapping non-process colors, the CMYK values of these non-process colors are added.

In a method in accordance with the invention, the second model is preferably created in another space than CMYK space. Advantageously, the model is created in a device independent space, such as CIELAB or, which is preferred, CIE XYZ. A space that has a one-to-one relation to a device independent space, such as sRGB, may also be used. Moreover, it is preferred to use another model than the simple addition of colorant values, in case of overlapping colors spot colors. In one embodiment of the invention, the spectral Neugebauer equations are used, as is discussed further below. Such a model in accordance with the invention is completely different from the customary simple addition in CMYK space. Preferably, to create the model, information is used on what non-process colors are present in the image. More preferably, also information is used on the occurrence of overlaps of non-process colors with each other and with process colors. Such information is included in the data of the image that is to be output, and can be extracted from the image by analyzing the image data.

An advantage of the invention is that spot colors, and especially the overlap of spot colors with each other or with other colors, are reproduced with higher color quality.

Another advantage is better reproduction of the transition between process colors and non-process colors.

One application of the invention is outputting an image on an output device. A preferred application is proofing an image on a proofing device, also called proofer, before it will be printed on another output device such as an offset press. The proofer is preferably an ink jet printer.

Further advantages and embodiments of the present invention will become apparent from the following description.

DETAILED DESCRIPTION OF THE INVENTION

5 If in a page description an object is defined by a non-process ink, a technique is required to reproduce the object in a way that is in agreement with the expectations of the customer. In the graphic arts, such a non-process ink is called a spot color; such an ink is used in the design of an image to create special color effects.

10 If the images designed for an offset system need to be simulated on a proofer or reproduced on another output system, profiles can be used to transfer the offset color values to a device independent color space whereas the profile corresponding to the output system
15 will transfer these color values further on to the colorant values of the output system. This method is used for the process colors (which are usually CMYK). As mentioned before, no color tables are available for spot colors and hence, the color values corresponding to colorant values of spot colors have to be predicted in another
20 way.

In graphic arts, a phenomenon that influences the reproduction of colors is dot gain. To reproduce an image by means of offset printing, color separations are made for the printing plates. If
25 only process colors are used, typically separations corresponding to the cyan, magenta, yellow and black ink are generated, resulting in four printing plates. However, if also additional spot colors are to be printed, for every spot color an additional separation has to be made, resulting in an additional printing plate. Each printing plate
30 is used to print one of the inks on a receiving substrate, such as paper. In printing, the dot size on paper appears to be larger than the dot sizes sent to the printing system. This effect is known as dot gain, and it is considered as a typical characteristic for the printing environment characterized for example by the ink, paper and
35 press combination. Therefore, if a spot color has to be simulated, also for this spot color some dot gain has to be taken into account

to predict the exact color. Hence, a technique is required that is able to predict the dot gain as if the colors were printed in offset. To predict dot gain accurately, a number of parameters have to be taken into account such as the types of ink and paper used. In practice dot gain can be predicted satisfactorily by specifying a standard dot gain curve. This curve represents the dot gain or dot loss as a function of the colorant values sent to the printing system.

10 A preferred embodiment of the invention is the following. An advantage of this embodiment is that it allows accurate reproduction of specific colors, such as spot colors and custom colors. Moreover, the overlap of such a specific color with another color, that may be a spot color, a custom color or a process color, may be
15 output with high color quality.

A model for the color mixing between spot colors or between spot colors and process colors is created based on an analysis of the image data, which include the spot color information. The model may
20 be made the first time it is needed and applied "on the fly" pixel per pixel; or the model may be made in advance before the image is processed and applied "on the fly" pixel per pixel; or the model may be made in advance, evaluated for a number of colorant combinations to obtain a color transformation table, and the table is applied
25 pixel per pixel by making use of interpolation techniques. The latter alternative is preferred, because it is computationally less intensive. In that case the complete image may be analyzed to check the color characteristics. The analysis detects the presence of non-process colors, as well as overlaps between non-process colors, and
30 between process colors and non-process colors. The non-process colors (e.g. spot colors, custom colors) then receive a special treatment. A model encompassing these colors is made, as discussed below.

35 **Spot color reproduction**

The reproduction of a spot color can be considered as a model for a 1-ink process. As printer model, it is preferred to use the Neugebauer equations, which are regarded as the basic model to predict color reproduction, e.g. in offset printing. However, the Neugebauer model does not predict dot gain. To simulate the dot gain behavior of a printing process, the well-known Yule-Nielsen correction can be used. The disadvantage of this correction is that it is highly dependent on the measurement technique, specifically the filters used for the color measurements and the model that is applied. Therefore, it is preferred to apply an improved dot gain correction that in general can be described by a model that modifies the colorant value itself. This modified colorant value is then input to the Neugebauer model. Such an improved dot gain correction, i.e. improved with respect to the Yule-Nielsen correction, may be obtained by making use of measured values. These measurement values may originate from the measurement of a printer target such as the IT8.7/3, IT8.7/4 or the ECI2002 target. Such a target can contain either colorimetric data such as CIELAB and XYZ, densities or spectral information. For one of these data sets, curve fitting is applied to the measured values in ordinate, as a function of the colorant values in abscissa. In the simplest way, the data for the 1-ink processes are taken from the measurement file and in between values are obtained by interpolation, e.g. linear interpolation. From the obtained curve, the dot gain values for CMYK can be determined. This can be calculated as the difference in dot percentage between the linear process between the 0% and 100% values and the fitted process. For example the dot gain for the 50 % value has the following characteristic: the measurement value of the 50 % value is equal to the measurement value of the (50+dotgain)% value in the linear process. For spot colors, the same dot gain behavior as for the process colors can be presumed. The Neugebauer model is then applied to the dot gain corrected colorant values. Dot gain corrected values in our example can be obtained by the sum of the dot percentage and its dot gain.

For a 1-dimensional process, as is the case for the reproduction of a single spot color, the Neugebauer model corresponds to linear interpolation between the device independent color values of the paper and those of the 100 % patch of the spot color. Preferably a
5 tristimulus space such as CIE XYZ is used for this interpolation; more preferably it is also used for the measurement values.

In a next step, the thus obtained device independent color values, e.g. in CIE XYZ, are transformed to the device dependent colorant
10 values of the output system. If the output system is then addressed with these device dependent colorant values, a reproduction of the image on the output system is made. The output system may be a proofing device, in which case a proof of the image is obtained. The transformation to the device dependent colorant values of the
15 output system is a so-called inverse transformation. If, for this inverse transformation, color tables are used, as within the ICC framework, sometimes the colors are desaturated and a rendering intent may have to be used that is not necessarily optimal for the rendering of spot colors. Therefore, another method is sometimes
20 preferred.

Analogously to the creation of the model for the output device discussed above, the inversion may be created on the fly or in advance a dedicated inversion table may be calculated. If
25 processing speed is required, the latter is preferred. If however, the transform has to be quite accurate, on the fly inversions are preferred in order to avoid interpolation errors. To obtain a combination of both, a dedicated table with a small step can be built in advance, in order to allow accurate calculation of the
30 transformation. If the colorant values for the output device are represented by 8 bit data, for the most accurate approach separations for all 256 colorant values are calculated in advance to be used to transform the spot color values in the device independent space to the colorant space of the output system.

In the case of two overlapping spot colors, only the colorimetric values for the two individual 100 % patches are given (such 100 % patches are also referred to as the solids). In this case too, a model is required to predict the colorimetric values of all possible combinations of overlap. However, in general not enough information is available to use a printer model. Let us take the Neugebauer model for a 2-ink process as an example. This model is given as follows:

$$X = X_p(1-c_1)(1-c_2)k_0 + X_1c_1(1-c_2) + X_2(1-c_1)c_2 + X_{12}c_1c_2$$

$$Y = Y_p(1-c_1)(1-c_2)k_0 + Y_1c_1(1-c_2) + Y_2(1-c_1)c_2 + Y_{12}c_1c_2$$

$$Z = Z_p(1-c_1)(1-c_2)k_0 + Z_1c_1(1-c_2) + Z_2(1-c_1)c_2 + Z_{12}c_1c_2$$

with (X_p, Y_p, Z_p) the XYZ values of the paper

(X_1, Y_1, Z_1) the XYZ values of the solid of the first spot color

(X_2, Y_2, Z_2) the XYZ values of the solid of the second spot color

(X_{12}, Y_{12}, Z_{12}) the XYZ values of the overlap of both spot colors

c_1 and c_2 the colorant value of the first and second spot color

(X, Y, Z) the XYZ values of the resulting color.

As can be seen from this formula, also the overlap of the two spot colors is needed.

This issue may be solved by using the transmission spectra of the solids and the reflectance curve of the paper to predict the colorimetric values of the 200 % ink overlap. The simplest model that can be used are the spectral Neugebauer equations. For even more accurate color predictions, corrections can be taken into account concerning several physical effects of light interactions at the ink surface, in the ink layers, between the ink layers and in the paper. Descriptions of these physical effects and corrections therefore can be taken from the specialist literature.

Besides this spectral modeling, it is preferred also to incorporate dot gain effect. As discussed above, this effect may be modeled

- 14 -

explicitly, e.g. by means of curves based on experimental data. Alternatively, dot gain values may be input by the user.

Similarly to the case of reproduction of a single spot color, the
5 obtained colorimetric values (e.g. in CIE XYZ) are separated into the device dependent colorant values of the output device.

Reproduction of process colors and a spot color

Also in the case of mixing process colors and a spot color, a model
10 is required that predicts the colors of all possible overlaps. This model is preferably continuous with respect to the model that is used in the forward color separation tables for the process colors only. As these tables are regular grids, the forward regular grid, for the four process colors CMYK, can easily be extended with the
15 spot color to obtain a 5-dimensional ink process. All the combinations of process inks in the forward table are maintained, and the solid spot color value is given. However, to be able to use interpolation schemes within color tables, at least all the corner points of the 5-dimensional colorant cube have to be specified.
20 Hence, all combinations of 0 % and 100 % for the process colors and the 100 % of the spot color have to be provided. To predict these combinations, a printer model is needed. Also in this case, a simple spectral Neugebauer process with additional dot gain modulation can be used. For even better prediction, more complex approaches
25 modeling different physical processes may be used. If a more accurate table is required, additional combinations of spot color values in between 0 % and 100 % with colorant values of the process colors can be determined with the printer model, and filled out in the table. To keep the 5-dimensional forward table as small as
30 possible, preferably only existing sampling points of the process colors are taken, with a minimum number of extra values for the spot color.

In this way a non-regular grid is obtained from which an irregular
35 localized model can be constructed; for more details we refer to EP-A-1 146 726, mentioned already above. Hence, a method is provided

to build a forward model that is a trade-off between taking into account a minimum of extra patches and hence a model that is as small as possible, and a more accurate model by filling out more colorant combinations resulting in a larger forward table.

5

For the inverse transformation from the colorimetric space to the colorant space of the output system, again, as discussed above, color tables may be used as within the ICC framework, or the inversion may be calculated on the fly, or a dedicated inverse separation table may be created once, i.e. in advance.

10

If only a limited number of combinations (i.e. overlaps) of the spot color and the process colors are present in the image, e.g. the spot color is only printed with cyan and magenta but not with yellow and black, then a smaller forward table can be constructed. In this way less colorant combinations have to be taken into account and a good continuity is achieved between process colors on the one hand and the combination of process colors and spot colors on the other hand.

15

If the image does not contain color gradations that are a combination of a spot color and the process colors, then the number of combinations of the spot color and process colors is quite limited. In that case, only for that limited number of combinations of process colors with the spot color, the resulting color has to be predicted, and the corresponding colorant values of the output system may again be calculated in advance or on the fly.

20

25

Reproduction of process colors and several spot colors

The previous approach to predict the colorimetric values for the overlap between one spot color and process colors can easily be extended to several spot colors.

30

It is known in the art to create a model for an output device, and to invert such a model, beforehand, i.e. before data on the image are available, which data include what colors and what overlapping colors occur in the image.

35

From the embodiments discussed above, it is clear that, in the present invention, a model may be created only when needed. Also the inversion on the fly may be used as needed. As computers get
5 faster and faster, this option becomes more and more interesting.

In one embodiment of the invention, the image is to be output directly on an output device. The output device may e.g. be an ink jet printer, or a printing device that uses printing plates, such as
10 an offset press. The non-process colors may then be converted to the process colors of the corresponding output device; combinations of only process colors do not need to be transformed.

In another embodiment of the invention, the image is to be output on
15 an output device such as an offset printing press, but first the image is to be simulated on a proofing device. In this case, first the printer model of the offset press is applied to the image, and then the inverse model of the proofer.

20 As mentioned already above, the model that is created preferably uses data on the image; these image data may be determined by analyzing the image, or data concerning the image may be input by the user. Take for example an image that contains a particular spot color yellow, and suppose that the color data, e.g. XYZ data, of
25 this yellow result in a dirty yellow being printed. The user can then override the color data for this yellow.

In a particular embodiment of the invention, the data of the image that is to be output are sent to the RIP, which stands for raster
30 image processor. Usually, the image data that are input to the RIP (e.g. in PostScriptTM format) are already separated in data in process colors, usually CMYK, on the one hand and in separate data, per spot color used, on the other hand.

35 The following example illustrates a set of operations that may then be performed in the RIP. First, a dot gain correction is applied.

- 17 -

Then, a model for the output device is created and applied to the spot colors. The spot color(s) are thus transformed to XYZ space. A rendering intent, that is specifically adapted to the spot colors, transforms the spot colors to another XYZ space, say X'Y'Z'.

5 Supposing that the image is to be proofed on a proofing device, a gamut mapping for the proofer is applied, followed by the inverse proofer model, which results in colorant values for the proofer. Possibly a smoothing step is applied.

10 In another embodiment of the invention, one or more of the preceding operations are omitted.

For combinations, i.e. overlaps, of spot colors with other spot colors or with process colors, it is preferred to use an accurate
15 model as set out above. However, especially if overlaps between three or even more colors occur, e.g. an overlap of a spot color with two process colors, a simplified "adding model" may also be used. For the color combinations that occur most, preferably an accurate model is applied. For the less occurring color
20 combinations, the spot colors may be converted to process color space, which is usually CMYK, by means of interpolation between the colorimetric values of the receiving substrate and those of the 100 % patch of the concerned spot color. The resulting CMYK values of the overlapping spot colors and process colors are then added.
25 In case a colorant value of more than 100 % is obtained, the colorant values are rescaled or, which is preferred, clipped.

The invention is not limited to embodiments described above. What was discussed especially for spot colors, also holds for other non-
30 process colors, such as custom colors. The process colors may be CMYK, they may be HexachromeTM colors, they may be six colors including CMYK and two colors selected from the group of orange, blue and green. Instead of a spectral Neugebauer model, another model may be used, such as polynomial fitting.

- 18 -

The invention includes a system and a method as disclosed above and as claimed in the appending claims. The invention also includes a printing plate and a printing plate precursor made by a method in accordance with the invention. A "printing plate precursor" is an
5 imaging material that can be used as a printing plate after one or more treatment steps, that include image-wise exposure and possibly processing. The invention further includes a color proof obtained by a method in accordance with the invention.

10 Having described in detail preferred embodiments of the current invention, it will now be apparent to those skilled in the art that numerous modifications can be made therein without departing from the scope of the invention as defined in the appending claims.

15 ■

[CLAIMS]

1. A method for outputting an image having a specific color on an output device, the method comprising the steps of:

5 -analyzing said image;

-creating a model for said output device, based on said analysis, wherein said model encompasses said specific color; characterized in that the method further comprises the step of:

10 -creating said model in a particular space having a one-to-one relation to a device independent color space.

2. The method according to claim 1 further comprising the step of:

-using said model for computing color values of said specific color in said particular space.

15 3. The method according to any one of the preceding claims wherein said specific color is a non-process color.

4. The method according to any one of the preceding claims further comprising the steps of:

20 -creating said model for an overlap of said specific color with another color.

5. The method according to claim 4 wherein said other color is selected from the group of a process color and a non-process color.

6. The method according to any one of the preceding claims wherein said particular space is CIE XYZ.

30 7. The method according to any one of claims 1 to 6 wherein said output device is an ink jet printer.

- 20 -

8. The method according to any one of claims 1 to 6 wherein said output device is a printer using printing plates.

9. The method according to any one of claims 1 to 8 further comprising the step of:

-creating a first inverse transformation from said particular space to a first colorant space of another output device.

10. The method according to claim 9 further comprising the step of:

-obtaining a first color separation of said image by said first inverse transformation.

11. The method according to claim 9 or claim 10 wherein said other output device is a proofing device.

12. The method according to any one of claims 9 to 11 wherein said other output device is an ink jet printer.

13. The method according to any one of claims 1 to 8 further comprising the step of:

-creating a second inverse transformation from said particular space to a second colorant space of said output device.

14. The method according to claim 13 further comprising the step of:

-obtaining a second color separation of said image by said second inverse transformation.

15. The method according to claim 14 when dependent on claim 8, the method further comprising the step of:

-exposing a printing plate precursor according to said second color separation.

16. A computer program comprising computer program code means adapted to perform the steps of the method according to any one of claims

- 21 -

1 to 14 when said program is run on a computer.

17. A computer readable medium comprising program code adapted to
carry out the method according to any one of claims 1 to 14 when
run on a computer.

18. A data processing system comprising means for carrying out the
steps of the method according to any one of claims 1 to 14.

19. A color proof obtained by the method according to claim 11 or
claim 12.

20. A printing plate obtained by the method according to claim 15.

21. A system for outputting an image having a specific color on an
output device, the system comprising:
-input means for inputting data of said image;
-means for creating a model for said output device based on said
image data, wherein said model encompasses said specific color.

22. The system according to claim 21 wherein said model is created in
a particular space having a one-to-one relation to a device
independent color space.

23. The system according to claim 22 wherein said particular space is
CIE XYZ.

24. The system according to any one of claims 21 to 23 further
comprising means for computing color values of said specific
color in said particular space, using said model.

25. The system according to any one of claims 21 to 24 wherein said
image data comprise data on said specific color.

- 22 -

26. The system according to any one of claims 21 to 25 wherein said specific color is a non-process color.

27. The system according to any one of claims 21 to 26 wherein said model encompasses an overlap of said specific color with another color.

28. The system according to claim 27 wherein said image data comprise data on said overlap.

29. The system according to claim 27 or claim 28 wherein said other color is selected from the group of a process color and a non-process color.

30. The system according to any one of claims 21 to 29 wherein said output device is an ink jet printer.

31. The system according to any one of claims 21 to 30 wherein said output device is a printer using printing plates.

32. The system according to any one of claims 21 to 31 wherein said system is a proofing device.

33. The system according to any one of claims 21 to 32 wherein said system is an ink jet printing device.

■

INTERNATIONAL SEARCH REPORT

Application No

03/50298

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04N1/60

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC, COMPENDEX

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2002/008880 A1 (DEWITTE HANS ET AL) 24 January 2002 (2002-01-24) paragraph '0066! - paragraph '0109!	1-33
A	US 5 933 578 A (MEIRESON BALDEWIN ET AL) 3 August 1999 (1999-08-03) the whole document	1-33
A	WO 00 74372 A (IMATION CORP) 7 December 2000 (2000-12-07) the whole document	1-33

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

10 December 2003

Date of mailing of the international search report

18/12/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Harde11, A

INTERNATIONAL SEARCH REPORT

Application No

PCT/EP 03/50298

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 2002008880	A1	24-01-2002	EP	1139654 A2	04-10-2001
US 5933578	A	03-08-1999	WO	9846008 A1	15-10-1998
			DE	69808062 D1	24-10-2002
			EP	0974225 A1	26-01-2000
			JP	2001519023 T	16-10-2001
			US	6483607 B1	19-11-2002
WO 0074372	A	07-12-2000	EP	1181812 A1	27-02-2002
			JP	2003501897 T	14-01-2003
			WO	0074372 A1	07-12-2000